

SWITCH  
LOGIQ



TEM

**TEM**

SWITCH  
LOGIQ

## SVEPRISUTNO SAMOPOUZDANJE

### Napravljeno za bilo koji prostor

Dizajn koji je prikladan za svaki prostor. Univerzalne linije sklopki ostavljaju svoj pečat u modernim radnim okruženjima ili u toplijim prostorima vašeg doma. Za svaku vašu želju obitelj sklopki LOGIQ nudi vam jednostavno i logično rješenje.

## OMNIPRESENT CONFIDENCE

### made for every room

A shape for every room. The switches have universal lines that leave a mark in both modern work environments as well as in cosy, comfortable living spaces. The LOGIQ family offers a simple and logical solution for your every wish.



## HARMONIJA BOJA Odaberite svoju nijansu

Obitelj LOGIQ odlikuje se logičnim izborom provjerenih i elegantnih nijansi boja koje korisnici najviše vole. Vi se ne morate prilagođavati, LOGIQ linija prilagođava se vama tako da uvijek možemo izraditi ton boje prilagođen vašim posebnim željama. Logično.

## H A R M O N Y O F C O L O U R S C h o o s e y o u r h u e

The LOGIQ family prides itself on its logical range of verified and elegant hues known and loved by our clients. Don't compromise, the LOGIQ family has you covered. We can always create the hue of colour in accordance with your special request. Logically.

■ **antracit /**  
anthracite

■ **titan /**  
titanium

■ **bijela-sjaj /**  
polar white



## NEOGRANIČENA MAŠTA

Sastavi svoju kombinaciju

## LIMITLESS IMAGINATION


Create your own combination

Obitelj LOGIQ omogućuje vam sastavljanje proizvoljnih kombinacija. Za jednostavno kombiniranje za vas smo izradili koristan dodatak koji će vam olakšati nizanje vodoravnih i okomitih linija. Takozvani sustav 55/55 omogućuje vam da se uvijek koristite istim univerzalnim elementima. Zna li što želite? Ne brinite se, LOGIQ sklopke čitaju vaše misli.

The LOGIQ family allows you to create your own combination. To make combining simple, we have created a useful system that supports the sequencing of horizontal and vertical lines. The so-called 55/55 system allows you to use the same universal elements every time. Know what you want? Don't worry, the LOGIQ switches can read your mind.








## JEDNOSTAVNO ZA NAJZAHTJEVNIJE

Obitelj LOGIQ su sklopke, regulatori, senzori, utičnice za sve svrhe i sve na jednome mjestu. Možete ih rabiti pojedinačno ili u nizu. Kao i svaka obitelj koja raste i razvija se, i dalje ćemo razvijati našu ponudu u skladu s vašim potrebama i željama. Volimo osluškiivati vaše želje i nudimo vam rješenje koje će biti jednostavan i logičan nastavak priče obitelji LOGIQ.

## SIMPLE FOR THE MOST DEMANDING

The LOGIQ family offers switches, regulators, sensors, and sockets for every purpose in one place. You can use these products individually or in a sequence. Just like every family that grows and develops, the LOGIQ family will continue to develop our range of products in accordance with your needs and wishes. We are happy to listen to you and offer a solution which will simply and logically continue the story of the LOGIQ family.






SVE NA JEDNOME MJESTU I VIŠE  
ALL IN ONE PLACE AND MORE

# LOGIČNA UGRADNJA

## LOGICAL INSTALLATION

LOGIQ je rješenje za sustav standardnih okruglih doza. S pomoću njega možete planirati jednostavne i zahtjevne instalacije, novogradnje i adaptacije. Sustav karakteriziraju bezvijačani kontakti, koji vam štede vrijeme tijekom ugradnje elemenata.

LOGIQ is a solution for the system of standardized round installations boxes. It can be used for simple as well as more demanding installations, new buildings and adaptations. The system is characterised by plug-in contacts which save time during installation of elements.




# DOBRO JE ZNATI GOOD TO KNOW



Sve su utičnice opremljene sigurnosnim sklopovima koji osiguravaju zaštitu od kontakta s naponom.

All the sockets are equipped with a safety shutters assuring the protection to live contacts.



Dobro osmišljena konstrukcija sklopki omogućuje jednostavno dodatnu indikaciju.

A well-planned switch construction makes easy illumination possible also subsequently.



Pouzdanost preklopa osiguravaju kontakti od legura srebra (AgNi).

Contacts made of silver alloy (Ag-Ni) guarantee safe switching.




Bezvijačni kontakti omogućuju brzo i pouzdano spajanje vodiča. Na isti kontakt možete pričvrstiti dva vodiča različitih promjera.

Plug-in contacts enable quick and reliable attachment of wires. Two wires of different diameters can be attached to the same contact.




Nožice omogućuju dublje pričvršćivanje (također preko keramičkih pločica itd.)

Fixing claws enable deeper fixing (also through ceramic tiles, etc.)



Sastavljive doze olakšat će vam rad. Prave udaljenosti su vam zajamčene.

Easy-fitting installation boxes will make your work easier. Proper lengths are guaranteed.








SQ11

PW


IN

01

XO

tip type	naziv description	tehnički opis technical data	boja colour	opcijski opis 1 optional data 1	opcijski opis 2 optional data 2	opcijski opis 3 optional data 3
SQ10	SKLOPKA JEDNOPOLNA SWITCH 1WAY	10AX 250V~	<input type="checkbox"/> PW bijela – sjaj polar white	 NT neutralna neutral	 01	XO bez okvira without cover plate
SQ11	TIPKALO JEDNOPOLNO PUSH BUTTON 1WAY	10A 250V~	<input type="checkbox"/> TI titan titanium	 IN indikator indicator	 02	
SQ22	SKLOPKA DVOPOLNA SWITCH 2POLE	16AX 250V~	<input type="checkbox"/> AT antracit anthracite		 03	
.	□.	.	.		.	.
.	.	.	.		.	.

SKLOPKA JEDNOPOLNA 10AX 250V~



- SQ10PWXO
- SQ10TIXO
- SQ10ATXO



- 10AX 250V~, tip SQ10
- usklađeno s normom EN 60669-1
- bezvijčano pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>

SWITCH 1WAY 10AX 250V~

- 10AX 250V~, type SQ10
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm<sup>2</sup>



SKLOPKA JEDNOPOLNA 10AX 250V~ \_\_ IN



- SQ10PWINXO
- SQ10TIINXO
- SQ10ATINXO



- IN indikator, bez neonske tinjalice
- 10AX 250V~, tip SQ10
- usklađeno s normom EN 60669-1
- bezvijčano pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>


SWITCH 1WAY 10AX 250V~ \_\_ IN

- IN indicator, without neon lamp
- 10AX 250V~, type SQ10
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm<sup>2</sup>





- SQ11PWXO
- SQ11TIXO
- SQ11ATXO



TIPKALO JEDNOPOLNO 10A 250V~


- 10A 250V~, tip SQ11
- usklađeno s normom EN 60669-1
- bezvijačno pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>

*PUSH BUTTON 1WAY 10A 250V~*

- 10A 250V~, type SQ11
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm<sup>2</sup>



- SQ11PWIN01XO
- SQ11TIIN01XO
- SQ11ATIN01XO



TIPKALO JEDNOPOLNO 10A 250V~ \_\_ IN 01


- IN 01 indikator zvona, bez neonske tinjalice
- 10A 250V~, tip SQ11
- usklađeno s normom EN 60669-1
- bezvijačno pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>

*PUSH BUTTON 1WAY 10A 250V~ \_\_ IN 01*

- IN 01 indicator bell, without neon lamp
- 10A 250V~, type SQ11
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm<sup>2</sup>



- SQ11PWIN02XO
- SQ11TIIN02XO
- SQ11ATIN02XO



TIPKALO JEDNOPOLNO 10A 250V~ \_\_ IN 02


- IN 02 indikator svjetla, bez neonske tinjalice
- 10A 250V~, tip SQ11
- usklađeno s normom EN 60669-1
- bezvijačno pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>

*PUSH BUTTON 1WAY 10A 250V~ \_\_ IN 02*

- IN 02 indicator light, without neon lamp
- 10A 250V~, type SQ11
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm<sup>2</sup>



- SQ22PWIN03XO
- SQ22TIIN03XO
- SQ22ATIN03XO




SKLOPKA DVOPOLNA 16AX 250V~ \_\_ IN 03


- IN 03 neutralna 0-1, bez neonske tinjalice
- 16AX 250V~, tip SQ22
- usklađeno s normom EN 60669-1
- vijčano pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>

*SWITCH 2POLE 16AX 250V~ \_\_ IN 03*

- IN 03 neutral 0-1, without neon lamp
- 16AX 250V~, type SQ22
- in accordance with EN 60669-1
- screw contacts 1.5-2.5mm<sup>2</sup>



- SQ50PWXO
- SQ50TIXO
- SQ50ATXO



SKLOPKA SERIJSKA 10AX 250V~

- 10AX 250V~, tip SQ50
- usklađeno s normom EN 60669-1
- bezvijačno pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>


*SWITCH 2GANG-1WAY 10AX 250V~*

- 10AX 250V~, type SQ50
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm<sup>2</sup>





- SQ51PWXO
- SQ51TIXO
- SQ51ATXO



#### TIPKALO SERIJSKO 10A 250V~


- 10A 250V~, tip SQ51
- usklađeno s normom EN 60669-1
- bezvijačno pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>

#### PUSH BUTTON 2GANG-1WAY 10A 250V~

- 10A 250V~, type SQ51
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm<sup>2</sup>



- SQ52PWNT09XO
- SQ52TINT09XO
- SQ52ATNT09XO



#### SKLOPKA ŽALUZIJSKA 10AX 250V~ \_\_ NT 09


- NT 09 neutralna gore-dolje
- 10AX 250V~, tip SQ52
- usklađeno s normom EN 60669-1
- bezvijačno pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>
- s mehaničkim blokiranjem istodobnog uključivanja

#### SWITCH SHUTTERS 10AX 250V~ \_\_ NT 09

- NT 09 neutral up-down
- 10AX 250V~, type SQ52
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm<sup>2</sup>
- with mechanical interblock



- SQ53PWNT09XO
- SQ53TINT09XO
- SQ53ATNT09XO




#### TIPKALO ŽALUZIJSKO 10A 250V~ \_\_ NT 09


- NT 09 neutralna gore-dolje
- 10A 250V~, tip SQ53
- usklađeno s normom EN 60669-1
- bezvijačno pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>
- s mehaničkim blokiranjem istodobnog uključivanja

#### PUSH BUTTON SHUTTERS 10A 250V~ \_\_ NT 09

- NT 09 neutral up-down
- 10A 250V~, type SQ53
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm<sup>2</sup>
- with mechanical interblock



- SQ60PWXO
- SQ60TIXO
- SQ60ATXO




#### SKLOPKA IZMJENIČNA 10AX 250V~


- 10AX 250V~, tip SQ60
- usklađeno s normom EN 60669-1
- bezvijačno pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>

#### SWITCH 2WAY 10AX 250V~

- 10AX 250V~, type SQ60
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm<sup>2</sup>



- SQ63PWXO
- SQ63TIXO
- SQ63ATXO



#### SKLOPKA IZMJENIČNA DVOSTRUKA 10AX 250V~


- 10AX 250V~, tip SQ63
- usklađeno s normom EN 60669-1
- bezvijačno pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>

#### SWITCH DOUBLE 2WAY 10AX 250V~

- 10AX 250V~, type SQ63
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm<sup>2</sup>







- SQ70PWXO
- SQ70TIXO
- SQ70ATXO



SKLOPKA KRIŽNA 10AX 250V~


- 10AX 250V~, tip SQ70
- usklađeno s normom EN 60669-1
- bezvijčano pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>

SWITCH INTERMEDIATE 10AX 250V~


- 10AX 250V~, type SQ70
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm<sup>2</sup>




SQ10  
SQ11




SQ22




SQ50  
SQ51




SQ52  
SQ53





SQ60+SQ60




SQ63+SQ63



SQ60+SQ70+SQ60





IA20

WH



tip type	naziv description	tehnički opis technical data	boja colour
IA10	NEONSKA TINJALICA NEON LAMP	230V~ 0,34W	<input type="checkbox"/> WH bijela white
IA20	LED SIGNALIZACIJA LED SIGNALLING UNIT	230V~ 0,40W	<input checked="" type="checkbox"/> BL plava blue
IA21	LED SIGNALIZACIJA LED SIGNALLING UNIT	24V AC/DC 0,20W	<input checked="" type="checkbox"/> RD crvena red
.	.	.	<input checked="" type="checkbox"/> GR zelena green
.	.	.	<input checked="" type="checkbox"/> OR narančasta orange


NEONSKA TINJALICA 230V~ 0,34W

IA10OR

- za indicaciju, osvjtljenje ili stalno osvjtljenje sklopke
- u kombinaciji s tipkom s indikatorom

NEON LAMP 230V~ 0,34W

- for indication, illumination or constant illumination of switch
- in combination with button with indicator




LED SIGNALIZACIJA 230V AC/DC 0,40W

IA20WH  
 IA20GR  
 IA20RD  
 IA20BL

- za indicaciju, signalizaciju ili stalnu signalizaciju
- u kombinaciji s tipkom s indikatorom

LED SIGNALLING UNIT 230V AC/DC 0,40W

- for indication, signalling or permanent signalling
- in combination with a button featuring an indicator




LED SIGNALIZACIJA 24V AC/DC 0,20W


IA21WH  
 IA21RD

- za indicaciju, signalizaciju ili stalnu signalizaciju
- u kombinaciji s tipkom s indikatorom

LED SIGNALLING UNIT 24V AC/DC 0,20W

- for indication, signalling or permanent signalling
- in combination with a button featuring an indicator






- IA22WH
- IA22RD

#### LED SIGNALIZACIJA 12V AC/DC 0,10W

- za indicaciju, signalizaciju ili stalnu signalizaciju
- u kombinaciji s tipkom s indikatorom

#### *LED SIGNALLING UNIT 12V AC/DC 0,10W*












- *for indication, signalling or permanent signalling*
- *in combination with a button featuring an indicator*




\* Indikacija /  
Indication

Signalizacija /  
Signalization

\* Stalna signalizacija  
Permanent signalling



\* spajanje prikladno za štedljive (CFL, LED) tinjalice /  
wiring scheme for energy saving lamps (CFL, LED)



tip type	naziv description	tehnički opis technical data	opcijski podatci 1 optional data 1
VQ10	UTIČNICA ŠUKO SOCKET SCHUKO	2P+E 16A 250V~	XO bez okvira without cover plate
VQ11	UTIČNICA ŠUKO+POKLOPAC SOCKET SCHUKO+COVER	2P+E 16A 250V~	
VQ12	UTIČNICA ŠUKO SOCKET SCHUKO	2P+E 16A 250V~ BV	
:	:	:	
:	:	:	


boja  
colour

<input type="checkbox"/> PW	bijela – sjaj polar white	<input type="checkbox"/> PT	bijela+prozirna white+transparent	<input type="checkbox"/> PP	bijela+bijela white+white
<input type="checkbox"/> TI	titan titanium	<input type="checkbox"/> TT	titan+prozirna titanium+transparent	<input type="checkbox"/> TI	titan+titan titanium+titanium
<input type="checkbox"/> AT	antracit anthracite	<input type="checkbox"/> AT	antracit+prozirna anthracite+transparent	<input type="checkbox"/> AA	antracit+antracit anthracite+anthracite
<input type="checkbox"/> RD	crvena red	<input type="checkbox"/> RT	crvena+prozirna red+transparent	<input type="checkbox"/> RR	crvena+crvena red+red
<input type="checkbox"/> GR	zelena green	<input type="checkbox"/> GT	zelena+prozirna green+transparent	<input type="checkbox"/> GG	zelena+zelena green+green
<input type="checkbox"/> OR	narančasta orange	<input type="checkbox"/> OT	narančasta+prozirna orange+transparent	<input type="checkbox"/> OO	narančasta+narančasta orange+orange




šuko – usklađen s normom EN 60884-1, CEE7 (lista standarda III)


schuko - in accordance with EN 60884-1, CEE7 (standard sheet III)



vijčano pričvršćivanje vodiča  
screw contacts



BV bezvijčano pričvršćivanje vodiča  
BV plug-in contacts



- VQ10PWXO
- VQ10TIXO
- VQ10ATXO
- VQ10RDXO
- VQ10GRXO
- VQ10ORXO

UTIČNICA ŠUKO 2P+E 16A 250V~ \_\_ XO

- vijčano pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>
- XO bez okvira
- 2P+E šuko
- 16A 250V~, tip VQ10
- zaštita od dodira kontakta

SOCKET SCHUKO 2P+E 16A 250V~ \_\_ XO

- screw contacts 1.5-2.5mm<sup>2</sup>
- XO without surround
- 2P+E schuko
- 16A 250V~, type VQ10
- shuttered live contacts




- VQ11PTXO
- VQ11TTXO
- VQ11ATXO
- VQ11PPXO

UTIČNICA ŠUKO+POKLOPAC 2P+E 16A 250V~ \_\_ XO

- vijčano pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>
- XO bez okvira
- 2P+E šuko+poklopac
- 16A 250V~, tip VQ11
- zaštita od dodira kontakta

SOCKET SCHUKO+COVER 2P+E 16A 250V~ \_\_ XO

- screw contacts 1.5-2.5mm<sup>2</sup>
- XO without surround
- 2P+E schuko+cover
- 16A 250V~, type VQ11
- shuttered live contacts



- VQ12PWXO
- VQ12TIXO
- VQ12ATXO
- VQ12RDXO
- VQ12GRXO
- VQ12ORXO

UTIČNICA ŠUKO 2P+E 16A 250V~ BV \_\_ XO


- BV bezvijčano pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>
- XO bez okvira
- 2P+E šuko
- 16A 250V~, tip VQ12
- zaštita od dodira kontakta

SOCKET SCHUKO 2P+E 16A 250V~ BV \_\_ XO

- BV plug-in contacts 1.5-2.5mm<sup>2</sup>
- XO without surround
- 2P+E schuko
- 16A 250V~, type VQ12
- shuttered live contacts



UTIČNICA ŠUKO+POKLOPAC 2P+E 16A 250V~ BV \_\_ XO



- VQ13PTXO
- VQ13TTXO
- VQ13ATXO
- VQ13PPXO

- BV bezvijčano pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>
- XO bez okvira
- 2P+E šuko+poklopac
- 16A 250V~, tip VQ13
- zaštita od dodira kontakta



SOCKET SCHUKO+COVER 2P+E 16A 250V~ BV \_\_ XO

- BV plug-in contacts 1.5-2.5mm<sup>2</sup>
- XO without surround
- 2P+E schuko+cover
- 16A 250V~, type VQ13
- shuttered live contacts

UTIČNICA ŠUKO DVOSTRUKA 2P+E 16A 250V~








- VQ16PW
- VQ16TI
- VQ16AT

- 2P+E šuko dvostruka
- 16A 250V~, tip VQ16
- usklađeno s normom IEC 60884-1, CEE7
- vijčano pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>
- zaštita od dodira kontakta

SOCKET SCHUKO DOUBLE 2P+E 16A 250V~

- 2P+E schuko double
- 16A 250V~, type VQ16
- in accordance with IEC 60884-1, CEE7
- screw contacts 1.5-2.5 mm<sup>2</sup>
- shuttered live contacts





KQ37

PW

XO

tip type	naziv description	tehnički opis technical data	boja colour	opcijski opis 1 optional data 1
KQ11	UTIČNICA TV-R ZAVRŠNA SOCKET TV-R END-LINE	1dB	<input type="checkbox"/> PW bijela – sjaj polar white	XO bez okvira without cover plate
KQ12	UTIČNICA TV-R PROLAZNA SOCKET TV-R THROUGHPASS	10dB	<input type="checkbox"/> TI titan titanium	
KQ16	UTIČNICA SAT-TV-R ZAVRŠNA SOCKET SAT-TV-R END-LINE	3dB	<input type="checkbox"/> AT antracit anthracite	
⋮	⋮	⋮		

#### UTIČNICA TV OSNOVNA 0dB



- KQ10PWXO
- KQ10TIXO
- KQ10ATXO

- TV osnovna
- prigušenje 0dB
- stražnji konektor – F standard

#### SOCKET TV BASIC 0dB

- TV basic
- reduction 0dB
- back connector – F standard



#### UTIČNICA TV-R ZAVRŠNA 1dB



- KQ11PWXO
- KQ11TIXO
- KQ11ATXO

- TV-R završna
- frekvenzijski raspon 5÷862 MHz
- prigušenje: R-1.5dB, TV-1dB
- usklađeno s normom EN 50083-1
- vijčano priključenje

#### SOCKET TV-R END-LINE 1dB

- TV-R end-line
- frequency range 5÷862 MHz
- reduction: R-1.5dB, TV-1dB
- in accordance with EN 50083-1
- screw contact







- KQ12PWXO
- KQ12TIXO
- KQ12ATXO

**UTIČNICA TV-R PROLAZNA 10dB**

- TV-R prolazna
- frekvenčni raspon 5÷862 MHz
- prigušenje: R-10dB, TV-10dB, prolaznost-2dB
- usklađeno s normom EN 50083-1
- vijčano priključenje

**SOCKET TV-R TROUGH-PASS 10dB**

- TV-R troughpass
- frequency range 5÷862 MHz
- reduction: R-10dB, TV-10dB, trough-2dB
- in accordance with EN 50083-1
- screw contacts




- KQ16PWXO
- KQ16TIXO
- KQ16ATXO

**UTIČNICA SAT-TV-R ZAVRŠNA 3dB**

- SAT-TV-R završna
- frekvenčni raspon 5÷2400 MHz
- prigušenje: R-1dB, TV-1.5dB, SAT-3dB
- usklađeno s normom EN 50083-1
- vijčano pričvršćivanje

**SOCKET SAT-TV-R END-LINE 3dB**

- SAT-TV-R end-line
- frequency range 5÷2400 MHz
- reduction: R-1dB, TV-1.5dB, SAT-3dB
- in accordance with EN 50083-1
- screw contacts



- KQ22PWXO
- KQ22TIXO
- KQ22ATXO

**UTIČNICA AUDIO 2xRCA**

- audio 2xRCA
- pričvršćivanje vodiča lemljenjem

**SOCKET AUDIO 2xRCA**

- audio 2xRCA
- soldering connection of cable




- KQ23PWXO
- KQ23TIXO
- KQ23ATXO

**UTIČNICA AUDIO ZA ZVUČNIKE**

- audio 2x Ø4mm
- za pričvršćivanje vodiča za zvučnike, utikača Ø4mm ili viljuškaste kableske stopice
- pričvršćivanje vodiča lemljenjem sa stražnje strane

**SOCKET AUDIO LOUDSPEAKERS**

- audio 2x Ø4mm
- to accommodate speaker wire, banana plug Ø4mm or spades
- soldering connection of cable at the back side



- KQ36PWXO
- KQ36TIXO
- KQ36ATXO


**UTIČNICA TEL KS RJ11 6/4**

- KS keystone standard pričvršćivanja
- RJ11 6/4
- usklađeno s normom IEC 60603-7

**SOCKET TEL KS RJ11 6/4**

- KS keystone fixing standard
- RJ11 6/4
- in accordance with IEC 60603-7






- KQ37PWXO
- KQ37TIXO
- KQ37ATXO

**UTIČNICA CAT5e KS RJ45 8/8**

- KS keystone standard pričvršćivanja
- CAT5e, RJ45 8/8
- usklađeno s normom IEC 60603-7

**SOCKET CAT5e KS RJ45 8/8**

- KS keystone fixing standard
- CAT5e, RJ45 8/8
- in accordance with IEC 60603-7




- KQ38PWXO
- KQ38TIXO
- KQ38ATXO

**UTIČNICA TEL KS DVOSTRUKA 2x RJ11 6/4**

- KS keystone standard pričvršćivanja
- 2x RJ11, 6/4
- usklađeno s normom IEC 60603-7

**SOCKET TEL KS DOUBLE 2x RJ11 6/4**

- KS keystone fixing standard
- 2x RJ11, 6/4
- in accordance with IEC 60603-7




- KQ39PWXO
- KQ39TIXO
- KQ39ATXO

**UTIČNICA CAT5e KS DVOSTRUKA 2x RJ45 8/8**

- KS keystone standard pričvršćivanja
- 2x CAT5e, RJ45 8/8
- usklađeno s normom IEC 60603-7

**SOCKET CAT5e KS DOUBLE 2x RJ45 8/8**

- KS keystone fixing standard
- 2x CAT5e, RJ45 8/8
- in accordance with IEC 60603-7




- KQ35PWXO
- KQ35TIXO
- KQ35ATXO

**UTIČNICA TEL LT RJ11 6/4**

- TEL LT vijak
- vijčano pričvršćivanje vodiča
- RJ11 6/4
- usklađeno s normom IEC 60603-7

**SOCKET TEL LT RJ11 6/4**

- TEL LT screw
- screw contacts
- RJ11 6/4
- in accordance with IEC 60603-7



- KQ40PWXO
- KQ40TIXO
- KQ40ATXO


**UTIČNICA CAT6s KS RJ45 8/8 SLIM**

- KS keystone standard pričvršćivanja
- CAT6s, RJ45 8/8
- usklađeno s normom IEC 60603-7

**SOCKET CAT6s KS RJ45 8/8 SLIM**

- KS keystone fixing standard
- CAT6s, RJ45 8/8
- in accordance with IEC 60603-7











- KQ41PWXO
- KQ41TIXO
- KQ41ATXO


**UTIČNICA CAT6s KS DVOSTRUKA 2x RJ45 8/8 SLIM**

- KS keystone standard pričvršćivanja
- 2x CAT6s, RJ45 8/8
- usklađeno s normom IEC 60603-7

**SOCKET CAT6s KS DOUBLE 2x RJ45 8/8 SLIM**

- KS keystone fixing standard
- 2x CAT6s, RJ45 8/8
- in accordance with IEC 60603-7






EQ15

PW

XO

tip type	naziv description	tehnički podaci technical data	boja colour	opsijski opis 1 optional data 1
EQ15	ZATAMNJIVAČ ROTACIJSKI IZMJEN DIMMER ROTATIVE 2WAY	RL 400W	<input type="checkbox"/> PW bijela – sjaj polar white	XO bez okvira without cover plate
EQ16	ZATAMNJIVAČ ROTACIJSKI IZMJEN DIMMER ROTATIVE 2WAY	RLC 400W	<input type="checkbox"/> TI titan titanium	
EQ19	ZATAMNJIVAČ ROTACIJSKI IZMJEN DIMMER ROTATIVE 2WAY	LED 100W	<input type="checkbox"/> AT antracit anthracite	
⋮	⋮	⋮		



- EQ15PW
- EQ15TI
- EQ15AT

### ZATAMNJIVAČ ROTACIJSKI IZMJEN RL 400W


- rotacijski s izmjeničnom sklopkom
- opterećenje RL, 40W – 400W
- mogućnost povezivanja s izmjeničnom sklopkom
- nije dopušteno povezivanje više zatamnivača
- usklađeno s normama EN 60669-1 i EN 60669-2-1
- bezvijačno pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>
- napajanje 230 V<sup>~</sup> 50 Hz
- priložen zamjenjivi osigurač

#### DIMMER ROTATIVE 2WAY RL 400W

- rotation control with 2-way switch
- load RL, 40W - 400W
- 2-way switch combination is possible
- more dimmers combination is not allowed
- in accordance with EN 60669-1 and EN 60669-2-1
- plug-in contacts 1.5mm<sup>2</sup>
- supply 230V<sup>~</sup> 50Hz
- replaceable fuse included



## ZATAMNJIVAČ ROTACIJSKI IZMJEN RLC 400W




- EQ16PWXO
- EQ16TIXO
- EQ16ATXO

- rotacijski s izmjeničnom sklopkom
- opterećenje RLC, 20W – 400W
- mogućnost povezivanja s izmjeničnom sklopkom
- nije dopušteno povezivanje više zatamnivača
- usklađen s normama EN 60669-1 i EN 60669-2-1
- bezvijčano pričvršćivanje vodiča 1.5mm<sup>2</sup>
- napajanje 230V~ 50 Hz
- elektronski osigurač

*DIMMER ROTATIVE 2WAY RLC 400W*

- rotation control with 2-way switch
- load RLC, 20W - 400W
- 2-way switch combination is possible
- more dimmers combination is not allowed
- in accordance with EN 60669-1 and EN 60669-2-1
- plug-in contacts 1.5mm<sup>2</sup>
- supply 230V~ 50Hz
- electronic fuse

## ZATAMNJIVAČ ROTACIJSKI IZMJEN LED 100W




- EQ19PWXO
- EQ19TIXO
- EQ19ATXO

- rotacijski s izmjeničnom sklopkom
- opterećenje: LED, 0-100W (max. 10 LED tinjalica)  
GLS, 10-250W
- mogućnost povezivanja s izmjeničnom sklopkom
- nije dopušteno povezivanje više zatamnivača
- usklađeno s normama EN 60669-1 i EN 60669-2-1
- bezvijčano pričvršćivanje vodiča 1.5-2.5mm<sup>2</sup>
- napajanje 230V~ 50 Hz
- priložen zamjenjivi osigurač


*DIMMER ROTATIVE 2WAY LED 100W*

- rotation control with 2-way switch
- load: LED, 0-100W (max. 10 LEDs)  
GLS, 10-250W
- 2-way switch combination is possible
- more dimmers combination is not allowed
- in accordance with EN 60669-1 and EN 60669-2-1
- plug-in contacts 1.5mm<sup>2</sup>
- supply 230V~ 50Hz
- replaceable fuse included


EQ15, EQ16, EQ19




EQ15, EQ16, EQ19




EQ15, EQ16, EQ19




EQ15, EQ16, EQ19




EQ16, EQ19



EQ16, EQ19




**EQ15 (40÷400W)**




- 1 - žarulja sa žarnom niti / incandescent lamp
- 2 - halogena žarulja / halogen lamp

**EQ16 (20÷400W)**



- 3 - klasični transformator / classical transformer
- 4 - elektronički transformator s mogućnošću prigušivanja / dimmable electronic transformer

**EQ19 (GLS 10÷250W ; LED 0÷100W)**




- 5 - LED tinjalica s regulacijom osvijetljenja / dimmable LED lamp



- EQ32PWXO
- EQ32TIXO
- EQ32ATXO


#### IR SKLOPKA 5A 230V~

- IR infracrvena sklopka
- napajanje: 230V~ ±10 % 50Hz
- Rele :5A/250V~ (zero crossing)
- razina zaštite: IP40
- presjek žica na kontaktnom terminalu: 0,75 – 2,5 mm<sup>2</sup>
- kut prepoznavanja: do 110° pri 20°C
- raspon prepoznavanja: približno 8 m pri 20°C
- prilagodljivost vremenskog trajanja: od približno 5 s do 12 min
- prilagodljivost osvjetljenja: od približno 5 do 200 LUX
- radna temperatura: od 0°C do +40°C
- nije prikladan za ugradnju u doze duboke 45 mm
- samo za unutrašnju uporabu



#### IR SWITCH 5A 230V~


- IR infrared switch
- supply voltage: 230V~ ±10 % 50Hz
- Relay :5A/250V~ (zero crossing)
- protection rating: IP40
- cross-section of wires at the contact terminal: 0.75 - 2.5 mm<sup>2</sup>
- detection angle: up to 110° at 20°C
- detection area: approx. 8 m at 20°C
- adjustability of duration: from approx. 5 s to 12 min
- adjustability of brightness: from approx. 5 to 200 LUX
- operating temperature: from 0°C to +40°C
- not suitable for installation in 45 mm deep boxes
- only for indoor usage



- EQ35PWXO
- EQ35TIXO
- EQ35ATXO


#### TERMOSTAT GRIJANJE 10A 230V~

- načina rada: grijanje
- napajanje: 230 V~, 50 Hz
- izlaz: 4 A (max. 10 A), 230 V~, 50 Hz
- izlazni priključak: NC (max. 10 aktuatora)
- raspon regulacije: od +5 °C do +30 °C
- histereza: 0,5 K
- zaštita: IP30
- vrsta senzora: bimetal
- vrsta električnog priključka: opružni kontakti
- vrsta vodiča:  
0,75 – 1,5mm<sup>2</sup> (meka žica) ali  
1,0 – 2,5 mm<sup>2</sup>(tvrda žica)



#### THERMOSTAT HEATING 10A 230V~


- operation mode: heating
- power supply: 230 V~, 50 Hz
- output: 4 A (max. 10 A), 230 V~, 50 Hz
- switching contact: NC (max. 10 actuators)
- regulation range: +5 °C to +30 °C
- hysteresis: 0,5 K
- protection: IP30
- sensor type: bimetal
- type of electrical connection: spring-loaded contacts
- type of conductors:  
0,75 – 1,5mm<sup>2</sup> (flexible-stranded core) or  
1,0 – 2,5 mm<sup>2</sup> (solid core)



- EQ36PWXO
- EQ36TIXO
- EQ36ATXO


### TERMOSTAT GRIJANJE / HLAĐENJE 5A 230~

- načina rada: grijanje / hlađenje
- napajanje: 230 V~, 50 Hz
- izlaz: 2 A (max. 5 A), 230 V~, 50 Hz
- izlazni priključak: preklopna sklopka (max. 5 aktuatora)
- raspon regulacije: od +5 °C do +30 °C
- histereza: 0,5 K
- zaštita: IP30
- vrsta senzora: bimetal
- vrsta električnog priključka: opružni kontakti
- vrsta vodiča: 0,75 – 1,5 mm<sup>2</sup> (meka žica) ili 1,0 – 2,5 mm<sup>2</sup> (tvrda žica)



### THERMOSTAT HEATING / COOLING 5A 230V~


- operation mode: heating / cooling
- power supply: 230 V~, 50 Hz
- output: 2 A (max. 5 A), 230 V~, 50 Hz
- switching contact: changeover switch (toggler, max. 5 actuators)
- regulation range: +5 °C to +30 °C
- hysteresis: 0,5 K
- protection: IP30
- sensor type: bimetal
- type of electrical connection: spring-loaded contacts
- type of conductors: 0,75 – 1,5mm<sup>2</sup> (flexible-stranded core) or 1,0 – 2,5 mm<sup>2</sup> (solid core)



- EQ37PWXO
- EQ37TIXO
- EQ37ATXO

### TERMOSTAT PODNO GRIJANJE 16A 230V~

- način rada: podno grijanje
- napajanje: 230 V~, 50 Hz
- izlaz: 2 A (max. 16 A), 230 V~, 50 Hz
- raspon regulacije: od +10 °C do +50 °C
- histereza: 1 K
- zaštita: IP30
- vrsta senzora: NTC u skladu s DIN EN 60730-2-1
- indikatori: crvena LED za grijanje i zelena LED za noćni način sa smanjenom funkcionalnošću
- vrsta električnog priključka: vijčani kontakti
- vrsta vodiča: 0,5 – 2,5 mm<sup>2</sup>



### THERMOSTAT FLOOR HEATING 16A 230V~

- operation mode: floor heating
- power supply: 230 V~, 50 Hz
- output: 2 A (max. 16 A), 230 V~, 50 Hz
- regulation range: +10 °C to +50 °C
- hysteresis: 1 K
- protection: IP30
- sensor type: NTC in compliance with DIN EN 60730-2-1
- indicators: Red LED for heating and green LED for night decrease mode
- type of electrical connection: Screw contacts
- type of conductors: 0,5 – 2,5mm<sup>2</sup>




TERMOSTAT GRIJANJE / HLAĐENJE 5A 230~



- EQ68PWXO
- EQ68TIXO
- EQ68ATXO


- načina rada: grijanje / hlađenje
- napajanje: 230 V~, 50 Hz
- izlaz: 2 A (max. 5 A), 230 V~, 50 Hz
- izlazni priključak: preklopna sklopka (max. 5 aktuatora)
- raspon regulacije: od +5°C do +30°C
- histereza: 0,5 K
- zaštita: IP30
- vrsta senzora: bimetal
- vrsta električnog priključka: opružni kontakti
- vrsta vodiča: 0,75 – 1,5 mm<sup>2</sup>(meka žica) ili 1,0 – 2,5 mm<sup>2</sup>(tvrda žica)




elektronika /

USB POWER SUPPLY UNIT 5V 3.0A


- for charging electronic devices via a standard USB port (also compatible with Apple devices)
- power supply: 100-230V~ 50/60Hz
- power consumption: 300mA at 100V~/150mA at 230V~
- standby power consumption: 30mW at 230V~
- nominal output voltage: 5 VCD (± 5%) SELV
- output ripple voltage: 150mV
- nominal output current: 3.0 A (±10%)
- connector type: USB A / USB C
- efficiency: maximum of 77%
- operating temperature: 0°C/+45°C (indoor use)
- IP protection class: IP20, indoor use only
- class device II
- overvoltage category (EN 62109): Class III
- screw contacts: max. 2.5 mm<sup>2</sup>
- device with a contact gap of at least 3mm
- in accordance with the EN 60950-1 and LVD & EMC directives




EQ15  
EQ16  
EQ19




EQ32




EQ35




EQ36



EQ37



EQ68



PQ10

PW

XO

tip type	naziv description	boja colour	opcijski opis 1 optional data 1
PQ10	PUNILO BLANK	<input type="checkbox"/> PW bijela – sjaj polar white	XO bez okvira without cover plate
PQ30	POKLOPAC TAE/TDO COVER TAE/TDO	<input type="checkbox"/> TI titan titanium <input type="checkbox"/> AT antracit anthracite	

PUNILO




- PQ10PWXO
- PQ10TIXO
- PQ10ATXO

- za pokrivanje praznih otvora  
*BLANK*  
- for filling up empty spaces




POKLOPAC TAE/TDO




- PQ30PW
- PQ30TI
- PQ30AT

- TAE ili TDO poklopac s vijkom  
*COVER TAE/TDO*  
- TAE or TDO cover with screw



PQ10






PQ30



OQ10

PW

tip type	naziv description	boja colour
OQ10	OKVIR LOGIQ 1 COVER PLATE LOGIQ 1	 PW bijela – sjaj polar white
OQ20	OKVIR LOGIQ 2 COVER PLATE LOGIQ 2	 TI titan titanium
OQ30	OKVIR LOGIQ 3 COVER PLATE LOGIQ 3	 AT antracit anthracite
:	:	
:	:	




	OQ10PW
	OQ10TI
	OQ10AT

#### OKVIR LOGIQ 1

- dekorativni pojedinačni okvir
- usklađeno s normom EN 60669-1

#### COVER PLATE LOGIQ 1

- decorative cover plate 1-gang
- in accordance with EN 60669-1




	OQ20PW
	OQ20TI
	OQ20AT

#### OKVIR LOGIQ 2

- dekorativni dvostruki okvir
- u skladu s EN 60669-1

#### COVER PLATE LOGIQ 2

- decorative cover plate 2-gang
- in accordance with EN 60669-1






- QQ30PW
- QQ30TI
- QQ30AT

### OKVIR LOGIQ 3

- dekorativni trostruki okvir
- u skladu s EN 60669-1

#### COVER PLATE LOGIQ 3

- decorative cover plate 3-gang
- in accordance with EN 60669-1




- QQ40PW
- QQ40TI
- QQ40AT

### OKVIR LOGIQ 4

- dekorativni četverostruki okvir
- u skladu s EN 60669-1

#### COVER PLATE LOGIQ 4

- decorative cover plate 4-gang
- in accordance with EN 60669-1




- QQ50PW
- QQ50TI
- QQ50AT

### OKVIR LOGIQ 5


- dekorativni peterostruki okvir
- u skladu s EN 60669-1

#### COVER PLATE LOGIQ 5

- decorative cover plate 5-gang
- in accordance with EN 60669-1







# TEM

TEM Čatež d.o.o.  
Čatež 13, 8212 Velika Loka  
Slovenija  
e: [info@tem.si](mailto:info@tem.si)  
w: [www.tem.si](http://www.tem.si)  
t: +386 (0)7 348 99 00

WJ1220JVE-T (18430)  
katalog 2023, 1. izdanje, 06/2023

**TEM**  
WWW.TEM.SI  
**JVE 2023**